



LENGTH  
Up to 40 ft

HEIGHT FORAGE  
5 - 8 ft

HEIGHT MANURE  
4ft

AXLE  
Tandem / Tridem

SUSPENSIONS  
Air

## COMBINATION TRAILER

THE ULTIMATE IN OPERATIONAL VERSATILITY.

An industry leader, this fully welded heavy-duty trailer easily switches from a manure spreader to a forage trailer.

Ideal for long hauls getting to the field, helping to reduce the amount of equipment you need. It comes standard with a Vertimax, with twin vertical augers and a hydraulic guillotine gate, spreads up to 55', and handles all manure types and other materials.

With the capacity of the JBS Combination Trailer, you'll never again need to stockpile spreadable manure in the field.

	CT3048	CT3248	CT3048	CT3448	CT4048
<b>Dimensions</b>					
Length (ft / m)	30' / 9.1m	32' / 9.8m	34' / 10.4m	36' / 11m	40' / 12.2m
Wall Height - Forage (ft / m)	5-8' / 1.5-2.4m				
Wall Height - Manure (ft / m)	4' / 1.2m				
Interior Box Width (in / m)	88" / 2.2m				
Level Capacity - Forage (ft <sup>3</sup> / m <sup>3</sup> )	1125 ft <sup>3</sup> / 31.9 m <sup>3</sup>	1920 ft <sup>3</sup> / 54.4 m <sup>3</sup>	2040 ft <sup>3</sup> / 57.8 m <sup>3</sup>	2160 ft <sup>3</sup> / 61.2 m <sup>3</sup>	2400 ft <sup>3</sup> / 68 m <sup>3</sup>
Level Capacity - Manure (ft <sup>3</sup> / m <sup>3</sup> )	900 ft <sup>3</sup> / 25.5 m <sup>3</sup>	960 ft <sup>3</sup> / 27.2 m <sup>3</sup>	1020 ft <sup>3</sup> / 28.9 m <sup>3</sup>	1080 ft <sup>3</sup> / 30.6 m <sup>3</sup>	1200 ft <sup>3</sup> / 34 m <sup>3</sup>
Heaped Capacity - Forage (ft <sup>3</sup> / m <sup>3</sup> )	2025 ft <sup>3</sup> / 57.3 m <sup>3</sup>	2160 ft <sup>3</sup> / 61.2 m <sup>3</sup>	2295 ft <sup>3</sup> / 65 m <sup>3</sup>	2430 ft <sup>3</sup> / 68.8 m <sup>3</sup>	2700 ft <sup>3</sup> / 76.5 m <sup>3</sup>
Heaped Capacity - Manure (ft <sup>3</sup> / m <sup>3</sup> )	1125 ft <sup>3</sup> / 31.9 m <sup>3</sup>	1200 ft <sup>3</sup> / 34 m <sup>3</sup>	1275 ft <sup>3</sup> / 36.1 m <sup>3</sup>	1350 ft <sup>3</sup> / 38.2 m <sup>3</sup>	1500 ft <sup>3</sup> / 4 2.5 m <sup>3</sup>
Suspension Capacity (lbs / kg)	50,000lbs / 22680kg			75,000lbs / 34020kg	
<b>Standard Features</b>					
Box	10 Gauge				
Suspension	Air				
Axle	Tandem or Tridem				
Tire Size	11R22.5				
Tire Options	Yes				
Tailgate Options	Swing or Barn Door				
Bulkhead	Standard				
Wheels	Steel or Aluminum				
Decal Package	Premium				
<b>Apron/Floor</b>					
Floor Chain	Long-Link 5/8" Grade 100 or WR78				
Floor Drive	Single				
Plantary Drive	Standard				
UHMW Plastic Floor	Yes				
Sprockets	Steel Idler Sprockets with Bronze Brushings				
<b>Beaters</b>					
Vertimax Vertical Beater	Yes				
Quick Attached Beater	Yes				
Hurricane Beater	Optional				
<b>Mechanical</b>					
Beater Protection	Shear Bolt				
Brakes	Air				
Steering Axle(s)	Optional				
Lift Axle	Optional				
<b>Add Ons</b>					
Front Fold Down	Optional				
Wall Extensions	Optional				
Working Lights	Optional				
Manual & Electric Tarp System	Optional				