



LENGTH
Up to 26ft

LEVEL CAPACITY
Up to 629 ft³

HEAPED CAPACITY
Up to 769 ft³

CARRYING CAPACITY
Up to 50,000lbs

EMPTY WEIGHT
Up to 21,500lbs

SUSPENSION
Spring

E-SERIES™ SPREADER

THE POWERFUL YET AFFORDABLE CHOICE.

Whether you run a large agricultural operation or a family farm, you'll get maximum work done quickly with our #1 best-selling spreader.

Featuring the same innovative technology and quality construction as our commercial models, The JBS E-Series Spreader comes with an upgraded long-link floor chain, quick-attach Vertimax beaters, and steel idler sprockets.

A heavy-duty yet affordable machine. The E-Series comes in a variety of sizes and can be loaded with even your smallest equipment.

	VMEC1636SA	VMEC1648	VMEC1848	VMEC2048	VMEC2248	VMEC2448	VMEC2648
Dimensions							
Overall Length (in / m)	294" / 7.47m	296" / 7.52m	319" / 8.1m	337" / 8.56m	361" / 9.17m	385" / 9.78m	409" / 10.39m
Overall Height (in / m)	118" / 3m	118" / 3m	118" / 3m	122" / 3.1m	122" / 3.1m	122" / 3.1m	122" / 3.1m
Overall Width (in / m)	135" / 3.43m	132" / 3.35m	135" / 3.43m	135" / 3.43m	135" / 3.43m	135" / 3.43m	135" / 3.43m
Inside Box Width (in / m)	78" / 1.98m	78" / 1.98m	78" / 1.98m	78" / 1.98m	78" / 1.98m	78" / 1.98m	78" / 1.98m
Inside Box Length (in / m)	168" / 4.27m	168" / 4.27m	192" / 4.88m	216" / 5.49m	240" / 6.1m	264" / 6.71m	288" / 7.32m
Load Height (in / m)	76" / 1.93m	89" / 2.26m	89" / 2.26m	91" / 2.31m	91" / 2.31m	91" / 2.31m	91" / 2.31m
Level Capacity (ft³ / m³)	317 ft³ / 9m³	369 ft³ / 10.5m³	421 ft³ / 11.9m³	473 ft³ / 13.4m³	525 ft³ / 15m³	577 ft³ / 16.3m³	629 ft³ / 17.8m³
Heaped Capacity (ft³ / m³)	425 ft³ / 12m³	454 ft³ / 12.8m³	517 ft³ / 14.6m³	581 ft³ / 16.5m³	645 ft³ / 18.3m³	706 ft³ / 20m³	769 ft³ / 21.7m³
Carrying Capacity (lbs / kg)	25,000 lbs / 11340 kg	50,000 lbs / 22680 kg	50,000 lbs / 22680 kg	50,000 lbs / 22680 kg	50,000 lbs / 22680 kg	50,000 lbs / 22680 kg	50,000 lbs / 22680 kg
Empty Weight (lbs / kg)	9,000 lbs / 4082 kg	10,500 lbs / 4763 kg	12,500 lbs / 5670 kg	14,500 lbs / 6577 kg	16,500 lbs / 7484 kg	18,500 lbs / 8391 kg	21,500 lbs / 9752 kg
Standard Features							
Box	10 Gauge						
Suspension	Spring						
Axle	Single	Tandem					
Tire Size	600/50-22.5						
Tire Options	Yes						
End Gate	Guillotine						
Bulkhead	Standard						
Hitch Type	Standard						
Decal Package	Basic						
Apron/Floor							
Floor Chain	Long-Link 5/8" Grade 100						
Cross Slats	Galvanized & Removable						
Floor Drive	Single						Dual
UHMW Plastic Floor	Yes						
Sprockets	Steel Idler Sprockets with Bronze Brushings						
Beaters							
Vertimax Vertical Beater	Yes						
Hurricane Beater	Optional						
Quick Attached Beater	Yes						
Hardox Lined Beater	No						
Mechanical							
HP Requirements	110-150	125-150	140-175	160-200	175-225	185-220	200-275
Beater Protection	Shear Bolt						
Hydraulic Brakes	Optional						
Rear Drive Shaft Diameter	2 3/16"						
Add Ons							
Silage Kit	Yes						
Wall Extensions	Optional						
Scale & Rate Controller	Optional						
Flight Protection System	Optional						