

LENGTH Up to 30ft

LEVEL CAPACITY Up to 1175 ft<sup>3</sup>

HEAPED CAPACITY Up to 1500 ft <sup>3</sup>

**CARRYING CAPACITY** 100,000 - 110,000 lbs

**GROUND PRESSURE** 11 PSI

SUSPENSION CASMO Track System

## **FLOAT-MAXX® SPREADER** EFFORTLESSLY GLIDE ACROSS EVERY FIELD.

Worried about ground pressure in your fields? Well don't be! The JBS Float-Maxx spreader has you covered; with only 11lbs per square inch of ground pressure. JBS Float-Maxx Manure Spreader has the lightest footprint of any manure spreader of its size.

Instead of having only 6 wheels, the JBS Float-Maxx has over 30ft of track on the ground at all times so you have be in the field even in the worst conditions.

The JBS Float-Maxx Manure Spreader has a massive carrying capacity of up to 110,000lbs.

	VMWB3042-50TR
Dimensions	
Overall Length (in / m)	534" / 13.56
Overall Height (in /m)	140" / 3.56
Overall Width (in / m)	126" / 3.2
Inside Box Width (in /m)	88" / 2.24
Inside Box Length (in / m)	336" / 8.53
Load Height (in / m)	105" / 2.67
Level Capacity (ft³/ m³)	1175 / 33.3
Heaped Capacity (ft <sup>3</sup> / m <sup>3</sup> )	1500 / 42.5
Carrying Capacity (lbs/ kg)	100,000 - 110,000 / 45 359 - 49 895
Empty Weight (lbs / kg)	33,000 / 14 969
Standard Features	
Box	10 Gauge
Suspension	CASMO Track System
Axle	Tracks
Tire Size	N/A
Tire Options	N/A
End Gate	Guillotine
Bulkhead	Standard
Hitch Type	Standard or Equal Angle
Decal Package	Premium
Apron/Floor	
Floor Chain	Long-Link 5/8" Grade 100
Cross Slats	Galvanized & Removable
Floor Drive	Dual
Planetary Drive	Yes
UHMW Plastic Floor	Yes
Sprockets	Steel Idler Sprockets with Bronze Brushings
Beaters	
Vertimax Vertical Beater	Yes
Hurricane Beater	Optional
Quick Attached Beater	Yes
Hardox Lined Beater	Optional
Mechanical	
Beater Protection	Shear Bolt
Hydraulic Brakes	Yes
Rear Drive Shaft Diameter	2 7/16"
Add Ons	
Silage Kit	Optional
Wall Extensions	Optional
Scale & Rate Controller	Optional
Flight Protection System	Optional

www.jbsequipment.com