



LENGTH
Up to 36ft

LEVEL CAPACITY
Up to 1410ft³

HEAPED CAPACITY
Up to 1610ft³

CARRYING CAPACITY
Up to 50,060kg

EMPTY WEIGHT
Up to 41,600lbs

SUSPENSION
50 Tonne Hydraulic

LOW-RIDER[®] SPREADER

A STEP ABOVE THE REST.

DELIVER A SMOOTH RIDE ON EVEN THE TOUGHEST TERRAIN.

The Low-Rider Manure Spreaders low center of gravity and large tires combined with the optional JBS electronic steering system to provide in-field stability that your large-scale or custom farming operation can count on.

These are the perfect spreader for customers who know exactly what it is they need to get the job done.

The newly engineered Quad Axle Low-Rider boasts a massive 64tonne Spring suspension! At 36' long the Quad Axle Low-Rider will allow you to spread more acres per load and get the day done faster and more efficiently.

	VMWB2630-34L	VMWB3042-48L	VMWB3042-50L	VMWB3642-64L
Dimensions				
Overall Length (in / m)	437" / 11.1m	486" / 12.34m	534" / 13.56m	555" / 14.1m
Overall Height (in / m)	146" / 3.63m	156" / 3.96m	153" / 3.89m	156" / 3.96m
Overall Width (in / m)	161" / 4.09m	161" / 4.09m	162" / 4.1m	161" / 4.09m
Inside Box Width (in / m)	82" / 2.1m	82" / 2.1m	82" / 2.1m	82" / 2.1m
Inside Box Length (in / m)	290" / 7.37m	336" / 8.53m	336" / 8.53m	408" / 10.36m
Load Height (in / m)	122" / 3.1m	132" / 3.35m	132" / 3.35m	136" / 3.45m
Level Capacity (ft³ / m³)	780ft³ / 22.1m³	1100ft³ / 31.2m³	1100 ft³/ 31.2m³	1410 ft³ / 41.1m³
Heaped Capacity (ft³ / m³)	918ft³ / 26m³	1260ft³ / 35.7m³	1450 ft³ / 41.1m³	1610 ft³ / 45.6m³
Carrying Capacity (lbs / kg)	68,000lbs / 30844kg	96,000lbs / 43545kg	100,000lbs / 45359kg	128,000lbs / 58060kg
Empty Weight (lbs / kg)	29,700lbs / 13472kg	37,300lbs / 17100kg	35,500lbs / 16103kg	41,600lbs / 18869kg
Standard Features				
Box	10 Gauge			
Suspension	Spring	Spring	Hydraulic	Spring
Axle	Tandem	Tridem	Tridem	Quad
Tire Size	750-60R-30.5			
Tire Options	No			
End Gate	Guillotine			
Bulkhead	Standard			
Hitch Type	Equal Angle			
Decal Package	Premium			
Apron/Floor				
Floor Chain	Long-Link 5/8" Grade 100			
Cross Slats	Galvanized & Removable			
Floor Drive	Dual			
UHMW Plastic Floor	Yes			
Sprockets	Steel Idler Sprockets with Bronze Brushings			
Beaters				
Vertimax Vertical Beater	Yes			
Hurricane Beater	Optional			
Quick Attached Beater	Yes			
Hardox Lined Beater	Optional			
Mechanical				
Beater Protection	Shear Bolt			
Hydraulic Brakes	Yes			
Steering Axle(s)	Yes			
Rear Drive Shaft Diameter	2 7/16"			
Add Ons				
Silage Kit	No			
Wall Extensions	Included			
Scale & Rate Controller	Yes			
Flight Protection System	Optional			