



**LENGTH**  
Up to 30ft

**LEVEL CAPACITY**  
Up to 780ft<sup>3</sup>

**HEAPED CAPACITY**  
Up to 27.6ft<sup>3</sup>

**CARRYING CAPACITY**  
Up to 72,000lbs

**EMPTY WEIGHT**  
Up to 25,000lbs

**SUSPENSION**  
Spring

## **NARROW BODY SPREADER** ENGINEERED TO HANDLE EVEN THE SMALLEST SPACES.

The JBS Narrow Body manure spreader gets the toughest jobs done faster and easier.

Engineered to operate in more confined spaces like feedlots, it features the same innovative technology and durable fully-welded components as our Wide Body machines.

The JBS Narrow Body Spreader doesn't compromise on field compaction or capacity.

Thoroughly field-tested, it's guaranteed to function at the highest standards, like every machine we build.

	VM2248-23	VM2448-23	VM2648-23	VM3048-36
<b>DIMENSIONS</b>				
Overall Length (in / m)	381" / 9.68m	405" / 10.29m	429" / 10.9m	477" / 12.12m
Overall Height (in / m)	140" / 3.56m			
Overall Width (in / m)	107" / 2.72m			
Inside Box Width (in / m)	78" / 1.98m			
Inside Box Length (in / m)	240" / 6.1 m	264" / 6.71m	288" / 7.32m	338" / 8.52m
Load Height (in / m)	111" / 2.82 m			112" / 2.84 m
Level Capacity (ft³ / m³)	572 ft³ / 16.2 m³	624 ft³ / 17.7 m³	676 ft³ / 19.1 m³	780 ft³ / 22.1 m³
Heaped Capacity (ft³ / m³)	715 ft³ / 20.2 m³	780 ft³ / 22.1 m³	845 ft³ / 23.9 m³	975 ft³ / 27.6 m³
Carrying Capacity (lbs / kg)	46,000lbs / 20865kg	46,000lbs / 20865kg	46,000lbs / 20865kg	72,000lbs / 32659kg
Empty Weight (lbs / kg)	16,500lbs / 7848kg	17,500lbs / 7938kg	18,500lbs / 8391kg	25,000lbs / 11340kg
Box Construction	10 Gauge			
<b>STANDARD FEATURES</b>				
Suspension	Spring			
Axle	Tandem			Tridem
Tire Size	550/45-22.5		700/40-22.5	
Tire Options	Yes		No	
End Gate	Guillotine			
Bulkhead	Standard			
Hitch Type	Standard or Equal Angle			
Decal Package	Premium			
<b>APRON/FLOOR</b>				
Floor Chain	Long-Link 5/8" Grade 100			
Galvanized & Removable Cross Slats	Yes			
Floor Drive	Single	Dual		
UHMW Plastic Floor	Yes			
Sprockets	Steel Idler Sprocket with Bronze Brushings			
<b>BEATERS</b>				
Vertimax Vertical Beaters	Yes			
Hurricane Beaters	Optional			
Quick Attach Beaters	Yes			
Hardox® Beaters	No			
<b>MECHANICAL</b>				
Beater Protection	Shear Bolt			
Hydraulic Brakes	Optional			
Steering Axle(s)	Optional			
Rear Drive Shaft Diameter (in / mm)	2 3/16" / 55mm			
<b>OPTIONAL UPGRADES</b>				
Silage Kit	No			
Wall Extensions	Optional			
Scale and Rate Controller Systems	Optional			