



LENGTH

Up to 34ft

LEVEL CAPACITY

Up to 1006ft³

HEAPED CAPACITY

Up to 1258ft³

CARRYING CAPACITY

Up to 100,000 lbs

EMPTY WEIGHT

Up to 32,000lbs

SUSPENSION

Spring or Hydraulic

WIDE BODY SPREADER

THE RIGHT TECHNOLOGY FOR THE MOST EFFICIENT FIELDWORK.

Whether you operate a family farm or a large agricultural enterprise, JBS Wide Body Spreaders can handle all types of manure.

Among the largest in today's market, they come in tandem and tridem axle models, feature highly maneuverable suspensions, and boast carrying capacities between 46,000lbs and 100,000lbs.

With our optional bolt-on silage kits, they are workhorses during silage season and ideal for stockpiling manure in the off-season. Able to spread all types of manure in all kinds of conditions, our equipment is built to handle any fieldwork you need to be done quickly and efficiently.

	VMWB2448 -23	VMWB2648 -34	VMWB3048 -36	VMWB3048 -48	VMWB3048 -50	VMWB3448 -48	VMWB3448 -50
Dimensions							
Overall Length (in / m)	413" / 10.5m	437" / 11.1m	485" / 12.32m	534" / 13.56m	534" / 13.56m	582" / 14.78m	582" / 14.78m
Overall Height (in / m)	140" / 3.56m	145" / 3.68m	146" / 3.71m	146" / 3.71m	146" / 3.71m	167" / 4.24m	167" / 4.24m
Overall Width (in / m)	125" / 3.18m	125" / 3.18m	125" / 3.18m	125" / 3.18m	125" / 3.18m	125" / 3.18m	125" / 3.18m
Inside Box Width (in / m)	88" / 2.24m	88" / 2.24m	88" / 2.24m	88" / 2.24m	88" / 2.24m	88" / 2.24m	88" / 2.24m
Inside Box Length (in / m)	264" / 6.71	288" / 7.32m	336" / 8.53m	336" / 8.53m	336" / 8.53m	384" / 9.75m	384" / 9.75m
Load Height (in / m)	111" / 2.82	117" / 2.97m	114" / 2.9m	117" / 2.97m	119" / 3.02m	116" / 2.95m	119" / 3.02m
Level Capacity (ft³ / m³)	710ft³ / 20.1 m³	800ft³ / 22.7 m³	888ft³ / 25.2 m³	888 ft³ / 25.2 m³	888ft³ / 25.2 m³	1006ft³ / 28.5 m³	1006ft³ / 28.5 m³
Heaped Capacity (ft³ / m³)	888ft³ / 25.2 m³	975ft³ / 27.6 m³	1110ft³ / 31.4 m³	1110ft³ / 31.4 m³	1110ft³ / 31.4 m³	1258ft³ / 35.6 m³	1258ft³ / 35.6 m³
Carrying Capacity (lbs / kg)	46,000lbs / 20865kg	68,000lbs / 30844kg	72,000lbs / 32659kg	96,000lbs / 43545kg	100,000lbs / 45359kg	96,000lbs / 43545kg	100,000 lbs / 45359kg
Empty Weight (lbs / kg)	24,500lbs / 12020kg	27,700lbs / 12564kg	23,500lbs / 10659kg	25,000lbs / 11340kg	26,500lbs / 12020kg	30,500lbs / 13835kg	32,000lbs / 14515kg
Standard Features							
Box	10 Gauge						
Suspension	Spring	Spring	Spring	Spring	Hydraulic	Spring	Hydraulic
Axle	Tandem		Tridem				
Tire Size	700/40-22.5	750/45R-26.5	700/40-22.5	750/45R-26.5	750/45R-26.5	750/45R-26.5	750/45R-26.5
Tire Options	No	Yes	No	Yes	Yes	No	No
End Gate	Guillotine						
Bulkhead	Standard						
Hitch Type - Standard or Equal Angle	Yes						
Decal Package	Premium						
Apron/Floor							
Floor Chain - Long-Link 5/8" Grade 100	Yes						
Galvanized & Removable Cross Slats	Yes						
Floor Drive	Dual						
Planetary Drive	Optional	Yes					
UHMW Plastic Floor	Yes						
Steel Idler Sprockets w/Bronze Brushings	Yes						
Beaters							
Vertimax Vertical Beater	Yes						
Hurricane Beater	Optional						
Quick Attached Beater	Yes						
Hardox Lined Beater	Optional						
Mechanical							
Beater Protection	Shear Bolt						
Hydraulic Brakes	Optional			Yes			
Steering Axle(s)	Optional			Yes			
Rear Drive Shaft Diameter	2 3/16"			2 7/16"			
Add Ons							
Silage Kit	Optional						
Wall Extensions	Optional						
Scale & Rate Controller	Optional						
Flight Protection System	Optional						