



LENGTH

Up to 36 ft

LEVEL CAPACITY

Up to 1410 ft³

HEAPED CAPACITY

Up to 1610 ft³

CARRYING CAPACITY

Up to 128,000 lbs

EMPTY WEIGHT

Up to 41,600 lbs

SUSPENSION

Spring or Hydraulic

LOW-RIDER® SPREADER

A STEP ABOVE THE REST.

DELIVERS A SMOOTH RIDE ON EVEN THE TOUGHEST TERRAIN.

The Tandem, Tridem and Quad Axle Low-Rider Manure Spreaders low center of gravity and large tires combined with the optional JBS electronic steering system to provide in-field stability that your large-scale or custom farming operation can count on.

These are the perfect spreader for customers who know exactly what it is they need to get the job done.

The newly engineered Quad Axle Low-Rider boasts a massive 64 tonne spring suspension! At 36' long the Quad Axle Low-Rider will allow you to spread more acres per load and get the day done faster and more efficiently.

LOW-RIDER SPECIFICATIONS

	VMWB2630-34L	VMWB3042-48L	VMWB3042-50L	VMWB3642-64L
Dimensions				
Overall Length	11.1 m 437 in	12.34 m 486 in	13.56 m 534 in	14.1 m 555 in
Overall Height	3.63 m 146 in	3.96 m 156 in	3.89 m 153 in	3.96 m 156 in
Overall Width	4.09 m 161 in	4.09 m 161 in	4.1 m 162 in	4.09 m 161 in
Inside Box Width	2.1 m 82 in	2.1 m 82 in	2.1 m 82 in	2.1 m 82 in
Inside Box Length	7.37 m 290 in	8.53 m 336 in	8.53 m 336 in	10.36 m 408 in
Load Height	3.1 m 122 in	3.35 m 132 in	3.35 m 132 in	3.45 m 136 in
Level Capacity	22.1 m³ 780 ft³	31.2 m³ 1,100 ft³	31.2 m³ 1,100 ft³	41.1 m³ 1,410 ft³
Heaped Capacity	26 m³ 918 ft³	35.7 m³ 1,260 ft³	41.1 m³ 1,450 ft³	45.6 m³ 1,610 ft³
Carrying Capacity	68,000 lbs 30,844 kg	96,000 lbs 43,545 kg	100,000 lbs 45,359 kg	128,000 lbs 58,060 kg
Empty Weight	29,700 lbs 13,472 kg	37,300 lbs 17,100 kg	35,500 lbs 16,103 kg	41,600 lbs 18,869 kg
Standard Features				
Box Construction	10 Gauge			
Suspension	Spring	Spring	Hydraulic	Spring
Axle	Tandem	Tridem	Tridem	Quad
Tire Size	750-60R-30.5			
Tire Options	No	Yes	No	Yes
End Gate	Guillotine			
Bulkhead	Standard			
Hitch Type	Equal Angle			
Decal Package	Premium			
Apron/Floor				
Long-Link 5/8” Grade 100 Floor Chain	Yes			
Galvanized & Removable Cross Slats	Yes			
Floor Drive	Dual			
UHMW Plastic Floor	Yes			
Steel Idler Sprocket with Bronze Brushings	Yes			
Beaters				
Vertimax Vertical Beaters	Yes			
Hurricane Beaters	Optional			
Quick Attach Beaters	Yes			
Hardox® Beaters	Optional			
Mechanical				
Beater Protection	Shear Bolt			
Hydraulic Brakes	Yes			
Steering Axle(s)	Yes			
Rear Drive Shaft Diameter	2 7/16 in 61.9 mm			
Add Ons				
Silage Kit	Optional			
Wall Extensions	Optional			
Scale & Rate Controller	Optional			
Flight Protection System	Optional			