JBS EQUIPMENT

LENGTH
Up to 30 ft

LEVEL CAPACITY
Up to 780 ft^3

HEAPED CAPACITY
Up to 975 ft^3

CARRYING CAPACITY
Up to 72,000 lbs

EMPTY WEIGHT
Up to 25,000 lbs

SUSPENSION
Spring

NARROW BODY SPREADER

ENGINEERED TO HANDLE EVEN THE SMALLEST SPACES.

Don't compromise on field compaction or capacity.

The Narrow Body Manure Spreader gets the toughest jobs done faster and easier with our spreader designed to operate in more confined spaces like feedlots.

Featuring the same innovative technology and durable fully-welded components as our Wide Body machines, it's guaranteed to function at the highest standard.

NARROW BODY SPECIFICATIONS

	VM3048-36
DIMENSIONS	
Overall Length	12.1 m | 477 in
Overall Height	3.56 m | 140 in
Overall Width	2.72 m | 107 in
Inside Box Width	1.98 m | 78 in
Inside Box Length	8.52 m | 338 in
Load Height	2.84 m | 112 in
Level Capacity	22.1 m^3 | 780 ft^3
Heaped Capacity	27.6 m^3 | 975 ft^3
Carrying Capacity	72,000 lbs | 32,659 kg
Empty Weight	25,000 lbs | 11,340 kg
STANDARD FEATURES	
Box Construction	10 Gauge
Suspension	Spring
Axle	Tridem
Tire Size	700/40-22.5
Tire Options	Yes
End Gate	Guillotine
Bulkhead	Standard
Hitch Type	Standard or Equal Angle
Decal Package	Premium
APRON/FLOOR	
Long-Link 5/8" Grade 100 Floor Chain	Yes
Galvanized & Removable Cross Slats	Yes
Floor Drive	Single
UHMW Plastic Floor	Yes
Steel Idler Sprocket with Bronze Brushings	Yes
BEATERS	
Vertimax Vertical Beaters	Yes
Hurricane Beaters	Optional
Quick Attach Beaters	Yes
Hardox® Beaters	No
MECHANICAL	
Beater Protection	Shear Bolt
Hydraulic Brakes	Optional
Steering Axle(s)	Optional
Rear Drive Shaft Diameter (in / mm)	2 3/16 in | 55 mm
OPTIONAL UPGRADES	
Silage Kit	No
Wall Extensions	Optional
Scale and Rate Controller Systems	Optional
Flight Protection System	Optional